

High Capacity Stacker

A high capacity stacker for straight or offset stacking. Thanks to a unique air venting system also normally hard to handle stocks are perfectly aligned. Rollaway trolley with battery operated lift for easy and ergonomic off-loading.

Plockmatic 101 HCS

DocuStack

PLOCKMATIC - YOUR PARTNER IN DOCUMENT FINISHING PRODUCTS



Plockmatic 101 DocuStack

The Plockmatic 101 HCS DocuStack is an addition to the DocuVac system. It has primarily been developed to meet the request from those customers requiring more stacking capacity.

The 101 HCS features a unique battery driven lift. When stacker is full or job completed, simply roll away the trolley to the next finishing station. Push the lift button to bring the stack from floor level to table your ergonomic work height. No more backbreaking lifts!



The stacking capacity is an impressive 400 mm (15,7") or roughly 4000 sheets. Thanks to length wise separation of sets it keeps up with the collator speed or 3600 sets per hour. Traditional stackers lower the systems speed and is often considered a bottleneck. The roll away trolley is battery driven and battery recharges automatically when stacker is docked.

Lower or raise the lift from trolley panel. Adjust the height to match yourself and next finisher or table. The 101 HCS comes with one stacker table as standard. Use an extra to increase productivity!



The Plockmatic 101 HCS DocuStack has full communication with the DocuVac 100 which means speed and paper size are automatically set. The integrated air venting system enables stacking of static material. When booklet making is required and the DocuBind 102 is a part of the system, there is no need to roll away the stacker – simply use the by-pass mode.



Specifications		Plockmatic 101 HCS DocuStack	
Stacking mode:		Offset / straight	
Capacity:		400 mm (15 3/4")	
Paper size:	Min	148 x 210 mm (5 3/4" x 8 1/4")	
	Max	320 x 457 mm (12 5/8" x 18")	
Paper weight:	Min	60 gsm (16 lb bond)	
	Max	240 gsm (65 lb bond)	
By pass function:		Yes	
Automatically recieving:		Yes	
Dimensions (HxWxD)		920 x 640 x 720 mm (36 1/4" x 25 3/16" x 28 5/16")	
Weight:		86 kg (190 lb) incl. lift	
Voltage:		100/115/125V 50-60 Hz 220/230/240V 50-60 Hz	

Manufactured by

PLOCKMATIC
International AB

Box 10025, S-121 26 STOCKHOLM-GLOBEN, SWEDEN
Tel: Int +46 8 602 50 00
Fax: Int +46 8 722 99 70

The machine design and specifications are subject to change without notice

Email: plockmatic@plockmatic.se
Web: www.plockmatic.se