

Plockmatic 47 PowerStacker



Model 47 PowerStacker is a high volume conveyor stacker for the output from the Inserter Model 45. However, it can also be used as a general output device for just about any type of paper feeding machine. No electrical interface is necessary - the unit is controlled by a built-in photocell. The unique side guides guarantees a very high capacity - up to 2,500 envelopes! The standard unit can be set up for both left hand and right hand operation.

Specifications

		Model 47
Capacity	C4 / 12*19" C5 / 6*9" DL / #10	up to 1500 up to 2500 up to 1200
Variable speed		Yes
Adjustable overlap		Yes
Run-out switch		Yes
Stacking	Adjustable side guides 115-357 mm (4 9/16"-14"). US#10, European DL up to DIN B4 in both orientations	
Table Height	Adjustable 635-792 mm (25"-31 3/16"). With optional low profile feet, 60 mm less	
Input height	Table height + 50-75 mm (2" 3").	
Width	440 mm (19 1/4") incl. control unit	
Length	1785 mm (68")	
Weight	58 kg (128 lb)	
Voltage	Universal power inlet. 100-240 VAC, 50-60 Hz, 1A	

The machine design and specifications are subject to change without notice

© Plockmatic International AB



Box 100 25, S-121 26 STOCKHOLM-GLOBEN, SWEDEN

Tel: Int +46 8 602 50 00, Fax: Int +46 8 722 99 70

Email: plockmatic@plockmatic.se, Website: <http://www.plockmatic.se>